

 [Print](#) | [Close Window](#)

Uncontrolled document as of November 25, 2008. Refer to website for up to date specifications.

CASES 1550 Case



Black



Silver



Orange



Yellow



OD Green*



Desert Tan

*OD Green available upon request

1550 Case

- Watertight, crushproof, and dust proof
- Easy open Double Throw latches
- Open cell core with solid wall design – strong, light weight
- O-ring seal
- Automatic Pressure Equalization Valve
- Comfortable rubber over-molded handle
- Stainless steel hardware and padlock protectors
- 2 level Pick 'N' Pluck™ with convoluted lid foam
- Personalized nameplate service available
- Lifetime Guarantee of Excellence

1550 Case Configurations

Cat. #	Description
1550	1550 Case
1550NF	1550 Case (No foam)
1554	1550 Case with Padded Dividers

1550 Case Specifications

Exterior Dimensions (L x W x D)

20.62" x 16.87" x 8.12" (52.4 x 42.8 x 20.6 cm)

Lid Depth

1.75" (4.4 cm)

Weight w/Foam

11.9 lbs. (5.4 kg)

Range Temperature

-10 / 210° F (-23 / 99° C)

Interior Dimensions (L x W x D)

18.43" x 14.00" x 7.62" (46.8 x 35.5 x 19.3 cm)

Bottom Depth

5.87" (14.9 cm)

Total Depth

7.62" (19.3 cm)

Weight w/o Foam

10.58 lbs. (4.8 kg)

Buoyancy Max.

69.89 lbs. (31.7 kg)

Personalized Nameplate Available

1550 Case Certificates

- IP67 (1 meter submersion for 30 minutes)
- MIL C-4150J • Def Stan 81-41/STANAG 4280 • ATA 300

1550 Case Accessories

Cat. #	Description
1550IP	Instapak Quick® RT
1550PF	Special Application Panel Frame
1551	4 pc. Replacement Foam Set
1552	Pick 'N' Pluck™ Sections Only (set of 2)
1553	Replacement O-ring
1555	Padded Divider Set Only

Pelican™ Products, Inc. Canada

10221 - 184 Street • Edmonton, Alberta T5S 2J4 • Phone: (780) 481-6076 • (866) 273-5422 • Fax: (780) 481-9586
Click to contact us • www.pelican.ca